

Declaration of Performance

No: 85858431-CPR

Version: 02

1. Unique identification code of the product type:

Akkit 301 Liquid sealing compound

2. Type, batch or serial number:

8585843, 8582241, lot number: see label text on the packaging

3. Intended use:

Standard liquid-processed, water-impermeable dispersion product for interior areas, DM.

4. Name and contact address:

Hornbach Baumarkt AG
Hornbachstrasse 11
76879 Bornheim / Germany

5. Name and contact address of the authorised representative:

not relevant

6. System:

System 3 for type test

7. Notified body:

The notified body, the Vienna City Magistrate, carrying identification number 1140, has performed the type test following system 3 and issued the following:
classification report: VFA 2011-0231.02

8. Notified body:

not relevant

9. Declared Performance:

Essential characteristics	Performance	Harmonized technical specification
Initial tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$	EN 14891:2012
Tensile adhesion strength after contact with water	$\geq 0,5 \text{ N/mm}^2$	
Tensile adhesion strength after thermal degradation	$\geq 0,5 \text{ N/mm}^2$	
Tensile adhesion strength after contact with lime water	$\geq 0,5 \text{ N/mm}^2$	
Tensile adhesion strength after frost / thaw storage cycles	$\geq 0,5 \text{ N/mm}^2$	
Impermeability to water	waterproof	
Crack bridging at normal temperatures	$\geq 0,75 \text{ mm}$	

10. Signed for and on behalf of the manufacturer by:

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.



Andreas Back, Director Quality Management and Environment
Bornheim, 31.07.2013

Appendix: Material safety data sheet according to regulation (EG) no. 1907/2006 (REACH)

ED012016-EN